



HARPER CHALICE GROUP LIMITED

8 Binns Close
Coventry
CV4 9TB
United Kingdom
Tel: 02476421 300
Fax: 02476 421 309
email: sales@harperchalice.co.uk
web: www.harperchalice.co.uk

VoiceMaster™

VoiceMaster™ electronic annunciation systems are the most efficient method of transmitting and communicating alarms and warning messages.

“It has now been proven that at least 98% of would be intruders or trespassers will leave immediately once they have been “Warned Off” by a verbal communication”.

VoiceMaster™ is a real voice messaging and communication system that uses human voice messages stored electronically to be recalled and transmitted whenever required. The systems are operated from 12 to 24v DC and are therefore compatible with most fire, security, access and monitoring systems. VoiceMaster™ systems are simple to operate, the message is triggered by applying a negative.

Typical applications include: -

Safety, Security, Fire, Evacuation, Public warning, Access announcements, Courtesy etc.

The Standard VM100 is pre-programmed with the following message: -

“Tones . . . You have been recognised as an intruder and your movements are being recorded on closed circuit video....LEAVE IMMEDIATELY!”

This message is transmitted every time the negative trigger voltage is applied.

VoiceMaster™ systems can be supplied with your own messages professionally recorded stored electronically and applied to a custom VoiceMaster™ unit of your choice during manufacture, or with a pre-recorded phrase from our extensive library. Alternatively we can supply VoiceMaster modules in circuit card form with a plug in chip containing a pre-recorded message or messages of your choice. The messages can then be recalled and transmitted whenever they are triggered.

VoiceMaster™ systems can be programmed with messages from 11 to 30 seconds including any tones. The messages can be programmed to operate once when the trigger voltage is applied or continually repeat until the trigger voltage is removed.

Single or multiple messaging units are available with independent trigger inputs for each pre-programmed message. Message duration can be up to 30 seconds from a single module. A 5-message unit is available with independent inputs and is capable of storing up to 30 seconds of messages. Trigger one will always take priority over the other inputs and is therefore ideal for fire and evacuation announcements.

VoiceMaster™ message systems can be personalised with your own unique messages or customised by using phrases from our existing phrase library, full details are available on request.



VoiceMaster™

We can professionally record personalised messages in our studio or alternatively we can electronically store your own good quality messages supplied to us on tape, CD or electronic transfer. This is particularly important for recordings in foreign languages or where regional accents or special tones are required.

VoiceMaster™ models available: -

VM110 VoiceMaster™ complete within weather proof siren speaker housing
Output Up to 110db (message dependent)
Duration Single message up to 15 seconds
Supply 12 – 24 v DC
Current 5 mA quiescent <1A average during message
Trigger Negative applied



VM305 VoiceMaster™ PCB module with up to 5 messages
Output 10 watts RMS into 8 ohm load
Duration Total message(s) length up to 30 seconds
Supply 12 – 24 v DC
Current 5 mA quiescent <1A average during message
Trigger 5 independent negative trigger inputs
Relay For auxiliary control applications a change over relay is supplied. The relay contacts operate when the 2nd input is applied.



VoiceMaster™ annunciation systems can be applied to almost any application. We shall be pleased to discuss any specific application you may have for the production of personalised messaging systems that meet your specification and operational requirements.

For further information please contact our sales office on Tel: +44 (0)24 7642 1300